



# BSS302

## Building Specification Sheet for ArmourColor Escenta Finish BSS302

<b>Product:</b>	ArmourColor Escenta Armourcoat Ltd. Morewood Close, London Road, Sevenoaks, Kent. TN13 2HU web: <a href="http://www.armourcolor.com">www.armourcolor.com</a>
<b>Location:</b>	(eg. Walls and ceilings to reception area and lift lobby).
<b>Drawings:</b>	Refer to drawings no. ...
<b>Background:</b>	Product for interior use only. Substrates should be prepared suitable for water-based paint application.
<b>Preparation:</b>	Coating is around 0.2mm thick and will follow contour of substrate. Surfaces should be sound and true with no hollows or bumps. Substrates must be free of curing compounds, dust, and other impurities such as oil, grease and salts and must be sealed with manufacturer's recommended primer. Remove all fixtures and fittings. Recommended background tolerance $\pm 1$ mm in 600mm and $\pm 3$ mm in 1800mm.
<b>Primer:</b>	Apply 1 or more coats of ArmourColor BaseColor Matt and allow to dry.
<b>Finish:</b>	Apply 1 coat of pre-mixed Armourcoat Escenta and finish as required. Apply ArmourColor Clearseal Gloss a minimum of 4-8 hours later (recommended in heavy traffic and vulnerable locations to improve abrasion resistance).
<b>Thickness:</b>	0.1 – 0.3 mm
<b>Colour:</b>	Escenta ref ... BaseColor Matt ref ... ArmourColor Clearseal Gloss ... yes / no
<b>Application:</b>	The system is to be supplied and applied by an ArmourColor Approved Applicator.

Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, the information should not be relied upon as a substitute for formal advice. Armourcoat Ltd, its employees and agents will not be liable for any loss or damage, of any kind, arising out of or in connection with the use of this document. Please refer to the company disclaimer for further details.  
HM BSS302 0608©

**Armourcoat Limited**  
Morewood Close London Road  
Sevenoaks Kent TN13 2HU United Kingdom  
Tel: +44 (0)1732 460 668 Fax +44 (0)1732 450 930  
Email: [technical@armourcoat.co.uk](mailto:technical@armourcoat.co.uk)

web: [www.armourcoat.com](http://www.armourcoat.com)