



BSS303

Building Specification Sheet for ArmourColor Tactite Finish BSS303

Product:	ArmourColor Tactite Armourcoat Ltd. Morewood Close, London Road, Sevenoaks, Kent. TN13 2HU web: www.armourcolor.com
Location:	(eg. Walls and ceilings to reception area and lift lobby).
Drawings:	Refer to drawings no. ...
Background:	Product for interior use only. Substrates should be prepared suitable for water-based paint application.
Preparation:	Coating is around 0.2mm thick and will follow contour of substrate. Surfaces should be sound and true with no hollows or bumps. Substrates must be free of curing compounds, dust, and other impurities such as oil, grease and salts and must be sealed with manufacturer's recommended primer. Remove all fixtures and fittings. Recommended background tolerance $\pm 1\text{mm}$ in 600mm and $\pm 3\text{mm}$ in 1800mm.
Primer:	Apply 1 or more coats of ArmourColor BaseColor Satin and allow to dry.
Finish:	Apply 2 coats of pre-mixed ArmourColor Tactite and finish as required.
Thickness:	0.1 – 0.3 mm
Colour:	Tactite ref ... BaseColor Satin ref ...
Application:	The system is to be supplied and applied by an ArmourColor Approved Applicator.

Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, the information should not be relied upon as a substitute for formal advice. Armourcoat Ltd, its employees and agents will not be liable for any loss or damage, of any kind, arising out of or in connection with the use of this document. Please refer to the company disclaimer for further details.

HM BSS303 0608©

Armourcoat Limited
Morewood Close London Road
Sevenoaks Kent TN13 2HU United Kingdom
Tel: +44 (0)1732 460 668 Fax +44 (0)1732 450 930
Email: technical@armourcoat.co.uk

web: www.armourcoat.com